

RUBYCi

ALL-IN-ONE CONVENIENCE RETAIL MANAGEMENT SOLUTION

POS, SITE CONTROLLER, BACK OFFICE MANAGEMENT

RubyCi is the latest POS solution offering from VeriFone. It is equipped with a functional site controller included in one piece of hardware providing fast, efficient, complete store management. The combination of POS and site controller makes this solution the only one of its kind in the marketplace. Now, site owners have the ability to consolidate as well as upgrade their operating technology at the same time.

RubyCi is equipped with a high capacity processor allowing it to grow in functionality as business needs change or expand. The sleek touch screen hardware allows for more counter space and a smaller footprint for each work station.



FUTURE OF C-STORE OPERATIONS

RubyCi offers the fastest total solution POS and site controller in the industry. This value based product offers versatile management software solutions as well for everything a convenience retail manager needs for optimum efficiency in store operations. RubyCi has the consistent VeriFone POS user interface for easy adoption and the same quality retailers have come to expect.

RUBYCi SITE SUPPORT

- Up to 16 fueling positions
- Up to 3 indoor POS stations

RubyCi SPECIFICATIONS

Processor	1.86 GHz Dual Core Atom CPU
Operating System	Secure Real-Time Linux
Safety	UL, cUL, CE Mark capability EMI: FCC Class A (USA) & CISPR 22 Class A (EU) ESD: IEC 1000 4-2 (8 KV contact, 4 KV air)
Memory	2GB Solid State SATA Flash 160GB HDD, scalable to 1+TB 2GB DDR3 RAM, scalable to 4GB
Dimensions	16"H x 14 3/4"W x 12"D
MSR	3-track MSR for reading loyalty and ID cards
Display	LED-backlit 15 inch TFT XGA high brightness display
Touch Screen	15 inch infrared touch screen with high transmissivity anti-glare glass
Communications	8 RJ-45, RS-232 serial ports with optional software controlled 12 Volt DTR power Diagnostic Panel for fast debugging; includes soft reset button, diagnostic console port, 7-segment status LEDs, heartbeat LED, and diagnostic switches
Environmental	Temperature: operating range 0-40° C, non-operating range -20 to 60° C Humidity: operating range 15% to 95%, relative humidity at 40° C
Connectivity	10/100/100 BaseT LAN port 6 USB ports 2 Cash Drawer ports with RJ-45 connectors for solenoid control DVI connector for second display Audio mic-in and line-out connectors 100/240V 50/60Hz operation